


2MP 60FPS IP BOX CAMERA

YUC-H6A6




Feature


- H.264 2MP/1080P 60fps, Sony Xarina solution/ Exmor CMOS sensor
- True WDR and digital image stabilizer
- Built-in IVS for Intrusion, Line-Crossing, Unattended-Object, Missing-Object face and tempering detection.
- Low noise and high sensitivity
- ESD & surge protection design
- Support SD card continuous recording up to 64G
- Day & night profile with separate setting
- Analogue output
- Mobile view support (push video)
- POE support
- ONVIF compliant




Intrusion



Line Crossing



Unattended Object



Missing Object



Dark frame



Real Wide Dynamic Range combined frame



Light frame



3D Noise Reduction

Specification

YUC-H6A6

Server	Compression	H.264 / MJPEG
	Resolution	1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144
	Traffic Control	64K ~ 10Mbps
	Max. Frame Rate	(60fps)1920x1080 , (30fps)1920x1080
	Safety	User-ID and password
	Protocols	Ipv4/v6 / HTTP / HTTPS / QoS Layer 3 level / FTP / SMTP / Bonjour / UPnP / SNMPv1/v2c/v3 / DNS / DDNS / NTP / RTSP / RTP / UDP / IEEE 802.1x / DHCP / Access list filtering
	Number of User	Max. 10 connections
	Storage Capacity	SD / FTP / NAS(Samba) / E-mail
	Alerting	SMTP / FTP / HTTP / SD
	Pre / Post Alarm	Pre(0,1,2,3,4,5) / Post(0,1,2,3,4,5,10) seconds
	Release for alarm	Motion detection / Object Detection / I/O / Schedule / Face detection / Tampering detection
Network Camera	Sensor	1/2.8" Megapixel SONY Exmor CMOS sensor
	Optical Lens	CS mount(DC driver)
	WDR	On / Off (Adjustable brightness , darkness and contrast)
	AGC	16X ~ 64X
	Shutter Time	Outdoor / Indoor / 1/30 , 1/50 , 1/60 , 1/100 , 1/125 , 1/250 , 1/500 , 1/1000 , 1/10000
	Min Illum	0.01 Lux(Color) / 0.005 Lux(B/W)
	Day / Night	Light sensor mode / Color mode(Day) / B/W mode(Night) / Times mode / Synchronize with DI input
Intelligent Video	DIS / Real WDR / Privacy Mask / 3D-De Noise Reduction / Motion Detection / Object Detection (Intrusion, Line-crossing, Unattended-object and Missing-object) / Face Detection / Tampering Detection	
Audio	Audio	2-way half duplex
	Audio Compression	G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps)
	Adjust Volume	Mic-in / Line-out web adjustable
	Audio In	Audio in or Mic built-in(Auto switch)
	Audio Out	3.5mm phone jack(Support 2-way)
Terminal	Network Interface	Ethernet(10Base-T/100Base-Tx) / PoE / WiFi(802.11/b/g/n)
	Video Interface	BNC, Video composit(NTSC/PAL)
	External Port	DI/ DO/ RS485
	SD Card	SD card(Up to 64GB)
General	Operation Voltage	DC 12V Max : 3.96W AC 24V Max : 4.8W PoE Max : 4.75W
	Dimen./Weight	65mm(φ) x 58mm(H) x 132mm(L) / 450g
	Operation Temp.	0°C ~ +45°C

Certificate : CE , FCC , RoHS

*No SD card slot & local storage function for Argentina

Dimension

