


Entry Level VGA Real Time Network Cube Camera

YUC-HS94A

Feature

- Ultra compact size & easy operation
- H. 264/ MPEG-4/ JPEG triple codec
- 2-way audio support for easiest communication
- Micro SD card for sudden network outage or alarm recording
- DI/DO for external alarm application
- Mobile surveillance
- PoE/ Wireless support
- ONVIF compliant



IP cam

YUC-HS94A

Camera Features	Image Pick-up Device	1/4" Progressive Scan CMOS sensor
	Effective Pixels (H x V)	640x480
	Lens Type	Fixed Lens
	Focal Length/ F-number	f: 4.3mm, F: 2.0
	Electronic Shutter Speed	1/50 (1/60) ~ 1/100,000 second(s) / Webpage Adjust
Image	Gain Control	AGC Adjustable (4x~64x)
	Network Compression	H.264/ MPEG-4/ M-JPEG
	Image Size	640x480, 320x240, 176x144
	Max. Frame Rate	30fps in all resolutions
Network Server	Intelligence Support	D-WDR, DNR, Motion Detection, Mask, VBR/CBR
	Protocols	Access list, Bonjour, DHCP, DDNS, FTP, HTTP, HTTPS, IPv4, IPv6 IEEE 802.1X, Multicast NTP, PPPoE, QoS/DSCP, RTSP, SAMBA, SMTP SNMP, UPnP, UPnP Forwarding
	Traffic Controls	32/48/64/96/128/196/256/320/384/448/512/576/640/704/768Kbps 1/1.5/2/2.5/3/3.5/4/6/8Mbps
	Number of Users	Max. 10 connections for singal video
Audio	Safety	User-ID and password
	Audio Communication	2-way-halfduplex
	Audio Compression	G.711(64Kbps)/ G.726(24Kbps/ 32Kbps)
	Frequency	300 Hz - 3.4KHz
	Audio In	Built-in Mic, Support 2-way audio
Interface	Audio Out	3.5mm, line out for external speaker
	Ethernet	RJ45 (10/ 100 Base-T)
	Wireless	802.11b/g/n
	Sensor I/O	DI/DO
General	Storage Device	Micro SD, FTP, Mail, NAS, and SAMBA
	Processors	ARM 9 ,32 bit RISC
	Memory	128MB-RAM, 16MB-Flash
	Power	PoE IEEE 802.3 af (Class 0)
	Operation Voltage	DC12V
	Dimen./Weight	93.7(H)x59(W)x45.5(D)mm 80g / 12pcs per carton
	Operation Temp.	-10°C ~ +45°C, relative moisture 20%-90%
	Included Accessories	CD/ IP recorder/ IP installer/ Installation guide/ Detail user manual/ Bracket



Product code: P-PoE, W-WiFi

*No SD/SDHC card for argentina.