

YUC-Hi26AM

2MP, 30fps, H.264/MJPEG, Auto Focus 4.2X



Product Info

2MP AUTO FOCUS IP VANDAL DOME CAMERA

YUC-Hi26AM

- H.264 2MP/1080P 30fps IP Camera
- Anti-fog / Corridor mode / Distortion correction smart function
- Tampering detection & 3 motion area setup
- Built-in 4.2X motorized zoom lens 2.8-12mm
- ESD & surge protection design
- Support SD card continuous recording up to 64G
- Day/night profile and smart IR
- Analogue output
- 3-Axis design included
- Vandal proof & weather proof IP66
- Heater built-in option
- Mobile view support (push video)
- POE support
- ONVIF compliant

| | | |
|-----------------------|---|---|
| Server | Compression | H.264/JPEG |
| | Resolution | 1920x1080 / 1280x720 / 640x480 / 320x240 / 176x144 |
| | Traffic Control | 32K ~ 8Mbps |
| | Max. Frame Rate | (30fps)1920x1080 |
| | Safety | User-ID and password |
| | Protocols | Ipv4/v6 / HTTP / HTTPs / QoS Layer 3 level / FTP / SMTP / Bonjour / UPnP / SNMPv1/v2c/v3 / DNS / DDNS / NTP / RTSP / RTP / UDP / IEEE 802.1x / DHCP / Access list filtering |
| | Number of User | Max. 10 connections |
| | Storage Capacity | Micro SD / FTP / NAS(Samba) / E-mail |
| | Alerting | SMTP / FTP / HTTP / Micro SD |
| | Pre / Post Alarm | Pre(0,1,2,3,4,5) / Post(0,1,2,3,4,5,10)seconds |
| | Release for alarm | Motion detection / I/O / Schedule / Tampering detection |
| Network Camera | Sensor | 1/2.7" Megapixel CMOS sensor |
| | Optical Lens | Motorized lens 2.8~12mm/ optical 4.2X zoom in |
| | View Angle | 36.9°~107.3°(H), 20.1°~56.4°(V) |
| | D-WDR | Off & 1~8 level |
| | AGC | 8X ~ 64X |
| | Shutter Time | Outdoor / Indoor / 1/30 , 1/50 , 1/60 , 1/100 , 1/125 , 1/250 , 1/500 , 1/1000 |
| | Min Illum | 0.05 Lux(Color) / 0.01Lux(B/W) |
| | IR LED / Range | 18pcs / 20M |
| Day / Night | Light senso mode / Color mode(Day) / B/W mode(Night) / Times mode / Synchronize with DI Input | |
| Intelligent Video | Anti-fog / Distortion Correction / Tampering Detection / IR Optimizer / D-WDR / Motion Detection / Privacy Mask / 3D-De Noise Reduction | |
| Audio | Audio | 2-way half duplex |
| | Audio Compression | G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps) |
| | Adjust Volume | Mic-in / Line-out web adjustable |
| | Audio In | Interior line in(Support 2-way) |
| | Audio Out | Interior line out(Support 2-way) |
| Terminal | Network Interface | Ethernet(10Base-T/100Base-Tx) / PoE |
| | Video Interface | BNC, Video composi(NTSC/PAL) |
| | External Port | DI / DO |
| | SD Card | Micro SD(Up to 64GB) |
| General | Operation Voltage | DC 12V Max: 4.20W(IR ON / 2.76W(IR OFF) PoE Max: 5.28W(IR ON) / 3.84W(IR OFF) |
| | Dimen./Weight | 137mm(∅) x 102mm(H) / 890 g |
| | Operation Temp. | -10°C ~ +50°C |
| | Waterproof | IP66 |
| | Vandal Proof | IK10 |