

YUC-Hi82M

4MP, 30fps, H.264/MJPEG, Varifocal



Product Info

4MP AUTO FOCUS IP VANDAL DOME CAMERA

YUC-Hi82M

- H.264 4MP (2688x1520) 30fps real time
- Privacy mask for 3 areas
- Advanced compression technology reduce 20% bandwidth
- Excellent night vision performance with low noise
- Built-in 4.2X motorized zoom lens 2.8-12mm
- ESD & surge protection design
- Support SD card continuous recording up to 64G
- 3 steps IR control
- 3-Axis angle adjust
- Vandal proof & weather proof IP66
- Mobile view support (push video)
- POE support
- ONVIF compliant

Server	Compression	H.264/JPEG
	Resolution	2688x1520@30fps, 1920x1080@30fps, 1280x720@30fps, 640x360@30fps

	Traffic Control	32K ~8Mbps
	Max. Frame Rate	(30fps)2688x1520
	Safety	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP
	Protocols	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour
	Number of User	Max. 10 connections
	Storage Capacity	Micro SD card / FTP / NAS(Samba) / E-mail
	Alerting	SMTP / FTP / Samba / Micro SD
	Pre / Post Alarm	Pre(0,1,2,3,4,5) / Post(0,1,2,3,4,5,10)seconds
	Release for alarm	Motion detection/ I/O / Schedule / Tampering Detection
Network Camera	Sensor	1/3" Megapixel CMOS sensor
	Optical Lens	Motorized lens 2.8~12mm/ optical 4.2X zoom in
	View Angle	35.68~102.56°(H), 19.06~55.52°(V)
	D-WDR	Off & 1 ~ 8 level
	AGC	8X ~ 64X
	Shutter Time	Outdoor / Indoor/ 1/30 , 1/50 , 1/60 , 1/100 , 1/125 , 1/250 , 1/500 , 1/1000
	Min Illum	0.08 Lux (Color), 0.03 Lux (B/W)
	IR LED / Range	14pcs / 20M
	Day / Night	Light sensor mode / Color mode(Day) / B/W mode(Night) / Times mode / Synchronize with DI input
Intelligent Video	D-WDR / Motion Detection / Privacy Mask / Noise Reduction/Tampering Detection/ IR Intensity	
Audio	Audio	2-way
	Audio Compression	G.711(64Kbps) / G.726(24Kbps) / G.726(32Kbps)
	Adjust Volume	Mic-in / Line-out web adjustable
	Audio In	Interior line in(Support 2-way)
	Audio Out	Interior line out(Support 2-way)
Terminal	Network Interface	Ethernet(10Base-T/100Base-Tx) / PoE
	Video Interface	BNC , Video composit(NTSC/PAL)
	External Port	DI / DO
	SD Card	Micro SD(Up to 64GB)
General	Operation Voltage	DC 12V Max: 6W(IR on) / 3.36W(IR off) PoE Max.: 8.64W(IR on) / 4.8W(IR off)
	Dimen./Weight	137mm(φ) x 102mm(H) / 890 g
	Operation Temp.	-20°C ~ +60
	Waterproof	IP66
	Vandal Proof	IK10